

# GS-9805-SD-W

---



## Smart Card IP Camera Support WiFi&SD Card

### Features

- smart IP camera designed for the small and middle-size shop, home using.
- Hand-hold wireless remote control
- Support 802.11 b/g network
- Through the remote control, the user can control the camera , Alarm ON/OFF, Emergency button, and the privacy protection function.
- User can view image through IE or DDNS to realize the real-time surveillance and play-back.
- Support internet listening, internet broadcasting, two-way audio function, built-in microphone and speaker
- Support local and internet storage, built-in Micro SD port.
- Integrated wireless alarm gateway function, support many PIR, curtain sensor, smoke detector, gas detector,
- Support emergency function for help, user can ask for help through remote control.
- Support alarm recording.
- Support privacy protection mode.
- Variety of internet protocols, Support IPv4/IPv6, HTTP, TCP, ICMP, RTP, UDP, IGMP, RTCP, SMTP, FTP, DHCP, DNS, DDNS、UPNP.
- Provide public standard API port, Support SDK integrated development.

# GS-9805-SD-W

## Structure



## Specs

Image Sensor	1/4" OV CMOS sensor, VGA Resolution, 1 Lux
Optional	8pcs, IR Distance: 6m
Lens	6mm fixed lens
Video Compression	H.264 baseline profile@Level 2.2
Video Resolution	VGA: 640x480, QVGA: 320x240
Video Parameters	Brightness, hue, contrast, saturation and image quality
Streaming Format	Optional Video Streaming or Audio & Video composite Streaming
Video Frame Rate	1~30F/S
Video Bit rate	16Kbit/S~4Mbit/S
Audio Input	1channel Microphone or linear input(configured by software) ,Input Impedance:1KOhms
Audio Compression	G.726
Audio Output	1 channel linear output
Audio talkback Input	1 channel Microphone input
Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, Ipsec, UpnP, RTP, RTCP
Network Interface	10Base-T/100Base-TX Ethernet port
	WiFi port (802.11b/g)
SD Card Interface	Support SD card Storage

Comm. Interface	1 RS485, 1 RS232,
Alarm Input	1 channel on/off input, supporting NO (normally open) or NC (normally close) sense.
Alarm Output	1 channel on/off output, 120VAC 1A/24VDC 1A
Input Power Supply	DC 12V, 1A
Maximum Power	Less than 6W
Operating Temperature	-10 ~ +55°C
Storage Temperature	-20 ~ +70 °C
Operating Humidity	10 ~ 85%
System Requirements	Operation System: Microsoft Windows 2000/XP/2003 Vista & 7 Browser: Microsoft Internet Explorer 5.x or above